


SECTION

LEGEND:

- (A) TECHO-BLOC PRECAST CONCRETE PAVER 3 1/8" (80 MM) OR 3 15/16" (100 MM) THICK CONFORMING TO ASTM C 936
- (B) STABILIZED SAND JOINT FILL CONFORMING TO ASTM C 144
- (C) SETTING BED (CONCRETE SAND) 1" (25 MM) THICK CONFORMING TO ASTM C 33
- (D) GEOTEXTILE, COVER JOINTS AND TURN UP AGAINST EDGE RESTRAINT
- (E) REINFORCED CONCRETE SLAB
- (F) GRANULAR BASE
- (G) SUBGRADE
- (H) EDGE RESTRAINT
- (I) DRAINAGE HOLE AT LOWEST ELEVATIONS, 3" (75 MM) DIA. FILL WITH FREE DRAINING AGGREGATE 1/2" (10 MM)

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5058-004.



PAVERS

PAVERS ON REINFORCED CONCRETE SLAB