



LEGEND:

- (A) TECHO-BLOC PRECAST CONCRETE SLAB 1 3/4" (45 MM) THICK MIN. CONFORMING TO CSA A231.1
- (B) SAND JOINT FILL CONFORMING TO ASTM C 144
- (C) SETTING BED (CONCRETE SAND) 1" (25 MM) THICK CONFORMING TO ASTM C 33
- (D) GEOTEXTILE 12" (300 MM) WIDE
- (E) EXTRA WIDTH EQUAL TO FOUNDATION THICKNESS
- (F) LAWN
- (G) TECHO-BLOC EDGE RESTRAINT
- (H) NAIL
- (I) COMPACTED GRANULAR BASE CONFORMING TO ASTM D 2940 THICKNESS ACCORDING TO PROJECT SPECIFIC CONDITIONS
- (J) GEOTEXTILE
- (K) SUBGRADE

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5058-011.

