


SECTION

LEGEND:

- (A) PILLAR CAP UNIT (SECURE WITH CONCRETE ADHESIVE)
- (B) PRESCOTT 2.25" UNIT SECURE EACH ROW WITH CONCRETE ADHESIVE
- (C) EMBEDMENT DEPTH 6" (150 MM) MIN.
- (D) 40 1/2" (1029 MM), HEIGHT PER PALLET, 45" (1143 MM), MAX. HEIGHT
- (E) GEOTEXTILE
- (F) COMPACTED GRANULAR BASE 6" (150 MM) THICK MIN. THICKNESS ACCORDING TO PROJECT SPECIFIC CONDITIONS

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
7. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT WWW.CADDETAILS.COM/INFO AND ENTER REFERENCE NUMBER 5058-121.



PILLARS

PILLARS (COLUMNS): PRESCOTT 2.25"